

Technical data sheet

PYROPLUG® Block foam block

Item number: 7202505



Soft, permanently elastic foam block for cable and combination insulation. Vertical and transverse installation to achieve different fire resistance classes. Can be combined with the two-component fire protection foam PYROSIT® NG. Can be used in solid ceilings and walls and in light-duty partitions and is approved for many installations. For interior application. CE-labelled construction product according to ETA-15/0803 for applications with fire resistance periods of up to 120 minutes.

Details on the applications can be found in the approval documents.

Protect the surface of the foam insulation against water in order to guarantee safe expansion in the event of fire. Coating with standard silicone is approved.



Permanently elastic, closed-pore foam

Master data

Item number	7202505
Type	FBA-B200-14
Description 1	Foam block
Description 2	intumescent
Manufacturer	OBO
Dimension	200x144x60mm
Colour	Brown
Material	Permanently elastic, closed-pore foam
Smallest sales unit	4
Unit of quantity	Piece
Weight	44.8 kg
Weight unit	kg/100 pc.

Technical data sheet

PYROPLUG® Block foam block


Item number: 7202505



Dimensions



Length	200 mm
Width	144 mm
Height	60 mm



Technical data

Fire protection version	Foam blocks
Shape	Rectangular
ROHS-conformant	yes
Accessories required	yes